### WS-C2960-24LT-L Datasheet





### Overview

WS- C2960-24TC-L is one of the Cisco Catalyst 2960 Series switches. This series support voice, video, data, and highly secure access. They also deliver scalable management as your business needs change. The Common Features are included: Enhanced security including Cisco TrustSec for providing authentication, access control, and security policy administration, Multiple Fast or Gigabit Ethernet performance options, Cisco EnergyWise for power management, Scalable network management.

#### **Quick Specs**

Figure 1 shows the appearance of the WS-C2960-24LT-L.



#### Table 1 shows the Quick Spec.

Product Code	WS-C2960-24LT-L
Enclosure Type	Rack-mountable - 1U
Feature Set	LAN Base
Uplink Interfaces	2 x 10/100/1000 TX uplinks
Ports	24 x Ethernet 10/100 ports with 8 PoE ports
Throughput	6.5 Mpps
Backplane Capacity	16 Gbps
DRAM	64 MB
Dimensions	1.73 x 17.5 x 9.3 in.
Package Weight	10.9 Kg

#### **Product Details**

Figure 2 shows the front panel of the Cisco 2960-24LT-L switch.



#### Note:

(1)	Mode Button
(2)	8 × Ethernet 10/100 PoE ports
(3)	16 × Ethernet 10/100 ports
(4)	2 dual-purpose uplinks

Figure 3 shows the back panel of the Cisco 2960-24LT-L switch.



#### Note:

(1)	RJ45 Console Port
(2)	RPS Connector
(3)	AC power connector

#### The Accessories

Table 2 shows some accessories of the WS-C2960-24LT-L.

Models	Description
GLC-LH-SM	GE SFP, LC connector LX/LH transceiver
GLC-SX-MMD	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
CAB-CONSOLE-RJ45	Console Cable 6ft with RJ45 and DB9F

### **Compare to Similar Items**

Table 3 shows the comparison of similar items.

Models	WS-C2960X-24TS-L	WS-C2960-24LT-L
Ports	24 x Ethernet 10/100/1000 Gigabit ports	24 x Ethernet 10/100 ports with 8 PoE ports
Uplinks	4 x 1G SFP	2 dual-purpose uplinks
Feature Set	LAN Base	LAN Base
FlexStack-Plus Stacking	Optional	N/A

### Get more information

Do you have any question about the Cisco Catalyst C2960-24LT-L switch?

Contact us now via Live Chat or sales@router-switch.com.

# Specification

WS-C2960-24LT-L Specifications		
Туре	Fixed	
Topology	Ethernet (10/100BaseTX) Ethernet (10/100/1000BaseT)	
Maximum Port density	8 10/100 PoE ports 16 10/100 ports	
Uplinks	2 10/100/1000 ports	
Modular/Expansion Slots	n/a	
Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Voice Enabled	
Form Factor	Fixed, Rack Mountable, Standalone/Clustering	
Dimensions	1.73 x 17.5 x 13 in.	
DRAM	64 MB	
	Features	
Specialized Service Modules	n/a	
	Security	
DHCP Snooping		
Dynamic ARP Inspection		
IP Source Guard		
RP Rate Limiters		
TCP Intercept		
802.1x		
Port Security		
Dynamic VLANs		

Private VLANs		
Private VLAN Edge		
Secure Shell		
SNMPv3		
Unicast RPF		
ACLs (L2-L4)		
Kerberos		
TACACS+		
RADIUS	0	
High Availability/Resilliency		
Hardware Redundancy	External Redundant Power Supply	
High Availability/Resilliency	PVST, Broadcast Suppression, Unicast Suppression, Mulitcast Suppression, Spanning Tree, Portfast, Uplink Fast, Backbone Fast, 802.1s, 802.1w	
Management		
Management features	SPAN, RSPAN, CiscoView, Cisco Discover Protocol (CDP), Virtual Trunking Protocol (VTP), Telnet Client, BOOTP, TFTP, CiscoWorks, CWSI, RMON, SNMP, Clustering, Web-Based Management	
Scalability		
WAN Interface Support	n/a	
Throughput	6.5 Mpps	
Backplane Capacity	16 Gbps	
Number of VLANs	255	

# Want to Buy

Order Now

Get a Quote

# Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of Cisco, Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.











## Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)

