

Overview

HP Retail Integrated 7-inch CFD



1. 7-inch diagonal LCD display

1. Increases Brightness
2. Decreases Brightness
3. Turns Power On and Off
4. Integrated Display Bezel Bracket
5. USB Connection



Shown attached to the top of monitor. Monitor sold separately.



Shown with retail solution, attached to the back of the monitor stand. All parts sold separately.

Overview

Model

HP Retail Integrated 7-inch CFD

F7A92AA

Introduction

Give customers a clear view of their transactions and share dynamic content at the point-of-sale with this 7-inch diagonal LCD display. Integrates easily into your retail solution adding video content and graphics to improve the customer experience.

Key Benefits

- Give customers a clear view of their transactions
 - Share engaging, colorful, dynamic content at the point-of-sale
 - Integrates easily into your retail solution
 - The USB bezel connector powers the CFD and eliminates the need for additional cabling
 - The edge-to-edge, bezel-less design is easy to clean, helps provide protection from dust, and creates a sleek, modern appearance.
-

Compatibility

The HP Retail Integrated 7-inch CFD is compatible with the HP RP7 Retail Systems model 7100 and 7800, and HP L6015tm and HP L6017tm Retail Touch monitors.

NOTE: Not all HP Retail system models are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP. Additional HP Care Pack Services options are available to extend warranty coverage.

Technical Specifications

General	Display Type	LCD, backlit LED
	Resolution	1024x600 (fixed)
	Dot Pitch	0.05(W) × 0.15(H) mm
	Active area	153.6(W) × 90.0(H) mm
	Contrast ratio	700:1 (max)
	Brightness	250 cd/m ²
	Response rate	Response rate 30ms (rise+fall time)
	Viewing Angle (of LCD Panel)	Left: 75°, Right: 75°, Top: 70°, Bottom: 75°
		Color Gamut
Mechanical	Dimensions (WxDxH)	185 x 53.5 x 125 (mm)
	Weight	0.69KG (CFD only)
	Adjustability	Tilt Range of Motion - 293°
	Color	HP Black
Interface/Connection	Interface	USB (mounted to the top display USB port only)
Power	Operating Voltage	5V
	Full Load Current	2.5W(DC +5V , 500mA)
	Idle Current	0.64W (DC+5V , 128mA)
Temperature Range	Operating	50° to 104° F (10 to 40° C) at 20% to 85% humidity (non-condensing at ambient)
	Non-operating	-22° to 149° F (-30° to 65° C) at 5% to 90% humidity (non-condensing at ambient)
Drivers	Windows	
Operating System Compatibility	Windows	<ul style="list-style-type: none"> • Windows 10 (32-bit and 64-bit) • Windows 10 IoT (32-bit and 64-bit) • Windows Industry 8/8.1 (32-bit and 64-bit) • Windows 8/8.1 Professional (32-bit and 64-bit) • Windows 7 Professional (32-bit and 64-bit) • Windows Embedded POS Ready 7 (32-bit and 64-bit) • Windows Embedded POS Ready 2009 • Windows XP Professional
	Option kit contents	HP Retail Integrated 7-inch CFD.

Summary of Changes

Date of change:	Version History:		Description of change:
June 16, 2016	From v1 to v2	Added	Callouts and back product picture, Windows 10
		Changed	Warranty statement,
		Removed	Documentation CD

© Copyright 2016-2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies.