## ThinkCentre M75s-1 SFF Platform Specifications

Processor	AMD Athlon PRO at	nd Ryzer	n 3 / 5 / 7 PR	O series pr	ocessor		Ethernet	Gigabit ethernet, Realtek RTL8111EPV, Wake on LAN®
	D	Cores /	Frequency	L2 / L3	Memory	Integrated	Ethernet (Opt.)	None
	Processor	Threads	(Base/Max)	Cache	Support (Up to)	Graphics	Manageability Security chip	DASH 10/1.1 Discrete TPM 2.0, TCG Certified
	Athlon PRO 300GE	2/4	3.4 / 3.4	1MB / 4MB		Radeon Vega 3	Security features	S • Security slot (in rear for optional • Power-on password
	Ryzen 3 PRO 3200G	4/4	3.6 / 4.0		DDR4-2933	Radeon Vega 8		Kensington® MicroSaver® cable) • Administrator password
	Ryzen 5 PRO 3400G	4/8	3.7 / 4.2	2MB / 4MB	DDR4-2933	Radeon Vega 11		Padlock loop     Hard disk password
Memory	64GB max, UDIMM, DDR4-2666*, four 288-pin DIMM sockets, non-ECC, dual-channel capable  * Memory may be underclocked to DDR4 -1866, DDR4-2133, or DDR4-2400 for the lower capability of memory controller in processor							<ul> <li>Smart USB protection, allows keyboard/mouse only, blocks all storage devices</li> <li>Optional smart cable clip to physically lock both keyboard and mouse</li> <li>Individual USB port disablement</li> <li>Optional chassis intrusion switch</li> </ul>
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm Some: M.2 SSD (2242 / 2280) / PCIe NVMe, PCIe 3.0 x2 or PCIe 3.0 x4 Some: DVD-ROM SATA 1.5Gb/s Drive, slim (9.0mm)						Keyboard	Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid)
Optical							Mouse	
•	Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm) Three onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model)						iviouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
Onboard SATA						ID preset only		
Media reader	Optional 7-in-1 media reader							Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)
Graphics	AMD Radeon™ Graphics in processor (only for some processors), uses main memory, DirectX® 12, one VGA, two DisplayPort™ (Onboard VGA and DP ports are only available on the models with integrated graphics), supports 3 independent displays, works along with AMD discrete graphics to support more displays; Max resolution: 4096x2160 (DP)@60Hz; Some: AMD Radeon™ 520, DirectX 12, 2GB GDDR5, PCle 3.0 x8 adapter, two DisplayPort, 30 watts (Max);  Max resolution: 4096x2160 (DP)@60Hz						Mechanical	<ul> <li>(WxDxH) 3.6" X 11.4" X 13.5"; 92.5mm X 290.5mm X 343.5mm</li> <li>Approx. 13.2 lb (6.0 kg), weight may vary by configuration</li> <li>Toolless cover, disk, optical, and extension card removal</li> <li>Optional dust filter</li> <li>Bay 1: Slim external ODD bay</li> <li>Bay 2: 3.5", internal, HDD/SSD</li> <li>Bay 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk)</li> <li>Slot 1: low-profile (length &lt; 150mm, height &lt; 68mm), PCle 3.0 x16</li> <li>Slot 2: low-profile (length &lt; 150mm, height &lt; 68mm), PCle 2.0 x1</li> <li>Slot 3: low-profile (length &lt; 150mm, height &lt; 68mm), PCle 2.0 x1</li> <li>Slot 4: low-profile (length &lt; 150mm, height &lt; 68mm), PCle 2.0 x1</li> <li>Slot 4: low-profile (length &lt; 150mm, height &lt; 68mm), PCl 3.0</li> <li>M.2 card slots: two (one for WLAN, one for SSD)</li> </ul>
Monitor cable	Max resolution: 4096x2160 (DF) @60H2  Optional DP to VGA, DP to DVI-D (single link), DP to dual DP, or DP to HDMI 1.4							
Chipset	AMD PRO 560 FCH						]	
	) 2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x microphone (3.5mm), 1x headphone (3.5mm)							
Front ports* (Opt.) Optional: 1x media reader Rear ports* (Std.) 2x USB 3.1 Gen1 (one support Smart Power-On), 2x USB 2.0, 1x serial (9-pin), 1x						x serial (9-nin) 1x	Power supply	Some: 180 watts, autosensing, 85% PSU
	ethernet (RJ-45), 1x VGA**, 2x DisplayPort**, 2x PS/2 ports (keyboard / mouse); 13 line-in (3.5mm), 1x line-out (3.5mm), 1x microphone (3.5mm) pt.) Optional: 2x USB 2.0, 1x parallel (25-pin), additional video ports available on					board / mouse); 1x	Some: 210 watts, autosensing, 85% PSU Some: 260 watts, autosensing, 92% PSU (only available via special bid)	
near ports (Opt.	optional graphics card						Limited warranty	1-year or 3-year, limited onsite service / service upgrades available
		oending on many factors, actual data transfer speed may be lower than theoretical speed ly available on the models with integrated graphics					Preload	Preloaded operating system  Some: Windows 10 Pro 64-bit  Some: Windows 10 Home 64-bit  Some: Windows 10 IoT Enterprise
Audio support	High Definition (HD) Audio, Realtek ALC662 / optional internal speaker (1 watt )					beaker (1 watt )		
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual ban Wi-Fi + Bluetooth 5.0 combo adapter, 2x2				`	,,		Some: Linux Ubuntu
	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2						Environment	ENERGY STAR® 7.0*, EPEAT™ Silver rating* (*not for non-OS models); ErP Lot 3; RoHS-compliant, WEEE
<b>5</b> 1	Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com
Bluetooth™	Some: Bluetooth 4.	2 / 5.0 w	vireless, integ	grated in Wi	-Fi + BT com	ibo adapter		
Note: The specifications above may not be available in all regions.  Lenovo, September 2019								